

External Grounding Kits



Lightning Protection for Connectors

PRODUCT FEATURES

- Fast and easy installation
- Large contact surface area
- IP68-classified and water-pressure proof tested down to 25 m
- No need for tape or other external weatherproofing
- Made of silver-plated brass and stainless steel
- Non-corrosive
- Reusable
- 10-year comprehensive warranty

PRODUCT PROFILE

The external grounding kit is designed to be mounted around the connector and to cause the connector itself to function as a grounding device.

This solution is very easy to install and provides extra protection at the feeder connector.



ARTICLE	EXGR-F012-AA00	EXGR-F078-AA00	EXGR-F114-AA00	EXGR-F158-AA00
CONNECTOR	xxxx-F012-A0	xxxx-F078-C0	xxxx-F114-AD00	xxxx-F158-AD00
COMPATIBILITY	xxxx-F012-H1 xxxx-S012-G1	xxxx-F078-AE02 xxxx-F078-AF00		
CONTACT AREA	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)
CABLE LENGTH	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)
OPERATING TEMP.	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C
PIECES IN BOX	50	50	50	50